

Specialty Cords

Braided Polyester Cord

Dia. Inches	Dia. MM	Tensile Lbs.	White		Black		50 Ft Hank - White	
			Part Number	Price	Part Number	Price	Part Number	Price
3/32	2mm	350	NEDAC03	0.06	NEDAC03BK	0.07	NA	NA
1/8	3mm	530	NEDAC04	0.07	NEDAC04BK	0.09	NEHANK04	5.27
5/32	4mm	730	NEDAC05	0.13	NEDAC05BK	0.15	NEHANK05	7.67
3/16	5mm	1,000	NEDAC06	0.14	NEDAC06BK	0.16	NEHANK06	



T-100

Dia. Inches	Dia. MM	Tensile Lbs.	Weight 100 FT	Spool Length	Part Number	Price
						Price
3/32	2mm	950	0.4	1500	NET10003	0.38
1/8	3mm	1,280	0.8	1200	NET10004	0.40
5/32	4mm	2,300	1	900	NET10005	0.51

Prices for Cut Lengths - Call for Special Prices on Full Spools.

Strong, low-stretch cord with a 100% Technora core with a braided polyester cover. This product took the place of Kevcord and is used for very low stretch leach lines by many sailmakers. Not spliceable.

Caution!

Harken's technical staff advises that, while sailing is an exciting sport, it calls for judgment and responsible use of sailboats and equipment. Loads can be significant and shock loading from heavy winds and seas can quickly magnify to extremes. Sailing Services agrees that all who select, install, or maintain sailboat hardware and rigging be encouraged to be cautious and mindful of such loads, and to carefully follow all installation, use and maintenance instructions. Failure to do so may result in grave bodily injury and risk to life.

When working aloft, all equipment should have a safety factor of 10:1 safe working load to actual load. A secondary safety line of equal rating must be used. We strongly advise that aloft rigging maintenance and installation be left to rigging professionals.

Specifications and descriptions contained in this catalog are subject to change without notification.

Call for Special Pricing Multiple Cut Lengths of Rope

Call for Special Pricing on Bulk Orders

Miscellaneous Line

Pro Shock Cord - Black

Diameter Inches	Part Number	Price
1/8	SHP04BK-SE	0.18
3/16	SHP06BK-SE	0.22
1/4	SHP08BK-SE	0.33
5/16	SHP10BK-SE	0.44
3/8	SHP12BK-SE	0.57

Filament rubber strands covered with a tight black polyester cover with excellent stretch and recover for long term use.



Messenger Line - Single Braid Polyester

Diameter Inches	Part Number	Description	Price
3/32	MESENGR03*	Braided Dacron - 3000 Ft Spool	59.10

*Add Color Code: BK (black), BL (blue), G (green), OL (olive), R (red), W (white), Y (yellow)

Breaking Strengths: Breaking Strengths of line are an average. Standard working loads should be no more than 20% of the rope's rated breaking strength. To calculate typical loads on sheets for genoas, jibs, end boom mainsheets, spinnaker guys and sheets, use this formula (except for multihulls): $(\text{Wind Speed})^2 \times .004 \times (\text{sail area in square feet}) = \text{Sheet Load at Clew in Pounds}$